



BZ-202F Titanium dioxide dispersant additive

Composition: Block modified polyether compounds

Appearance: Colorless transparent liquid

Active ingredient: 60%

Solvent: PMA

Application scope: industrial coatings, wood coatings, automotive coatings, water-based coatings

Recommended dosage: Titanium dioxide: 1-3%; organic pigment: 3-10%; carbon black: 20-40%; to the full amount of: 0.1-0.5%

Dosage: In order to get the full effect, it is recommended to add it in two times before and after.

Characteristics and advantages:

It has excellent dispersing whiteness for titanium dioxide, good wetting and dispersing and viscosity reduction, and will not produce flocculation after uniform dispersion.

It has good effect on the wetting and dispersing and liquidity of pigments (such as red, phthalocyanine blue, phthalocyanine green, etc.) of all kinds of color paste.

It also has good dispersion and surface tension reduction effect in water-based industrial paint and wood paint.

Package: 25KG non-recycled blue plastic drum.

Before the product is completely empty, the lid should be tightly closed after use.

Storage: Keep away from heat and light source and keep away from light.

Precautions: Please carefully evaluate the relative usage amount before use.

The above information is based on the product, due to the producer's formula, production process, construction conditions are different, the above statement is for reference only.

The company does not assume any legal responsibility, please test the dosage before use.

The company has the right to improve its own products, any changes in its specifications, without prior notice.